

The built-in USB communication port enables the unit to interact with bundled software to communicate with your operating system. It is also fitted with Telephone, Modem and Network connections to protect your system from “spikes”.

Categories: [Meissner](#), [XT Series](#).

- [Description](#)

Product Description

Features

- Microprocessor control guarantees high reliability.
- Equipped with Boost and Buck AVR.
- DC Start Function.
- Auto restart upon AC recovery.
- Provides AC Overload protection.

Specifications

MODEL		XT1200
CAPACITY	VA / W	1200VA / 600W
	Voltage	230V AC
	Voltage Range	170 – 280V AC
	Frequency	>40Hz (Auto Sensing)
OUTPUT	Voltage	230V
	Voltage Regulation	± 10% (Battery Mode)
	Frequency	50Hz
	Frequency Regulation	± 1Hz (Battery Mode)
	Output Waveform	Modified Sine Wave
BATTERY	Battery Type	12V / 7Ah x 2
	Recharge Time	6 Hours (max) to 90% after complete discharge
TRANSFER TIME	Typical	6 – 10ms
INDICATOR	Fault	Green Lighting
	Battery Mode	Green Lighting
	AC Mode	Yellow Flashing
	Normal	Red Lighting
AUDIBLE ALARM	Fault	Sounding every 10 seconds
	Overload	Sounding every 1 second
	Low Battery	Sounding every 0.5 second
	Back-Up Mode	Continuously Sounding
PROTECTION	Full Protection	Discharge, Overcharge and Overload Protection
PHYSICAL	Dimensions (mm)	345 (D) x 133 (W) x 183 (H)
WEIGHT	Nett Weight	9.6 Kgs
ENVIRONMENT	Operating Environment	0°C – 40°C
	Noise Level	Less than 50dB
BACKUP TIME	PC load with 15"	30 – 40 minutes